



Quality is Behind the Diamond

RUGGED

- 6 Year Warranty
- Stored Pressure Design
- Dependable Drawn Steel Cylinders
- Hydrographic Dip Process with Clear Coat Finish
- All Metal Valve Construction
 - Anodized Aluminum Valve Body
 - Anodized Aluminum Handle & Lever
- Temperature Range -65°F to 120°F

USER FRIENDLY

- Easy and Economical to Maintain and Service
- Large Loop Pull Pin
- Bar Coded and Bi-lingual Labels

OPTION

- USCG Approved with Bracket Listed on UL Label



MODEL B417T
EVO™

MODEL B417T
MUDDY GIRL™

ABC or Multi-Purpose extinguishers utilize a specially fluidized and siliconized mono ammonium phosphate dry chemical. It chemically insulates Class A fires by melting at approximately 350°F and coats surface to which it is applied. It smothers and breaks the chain reaction of Class B fires and will not conduct electricity back to the operator.

AGENT TYPE	ABC DRY CHEMICAL	
VALVE TYPE	ANODIZED ALUMINUM	ANODIZED ALUMINUM
DESIGN	NOZZLE	NOZZLE
MODEL NUMBER	B417T EVO™	B417T MUDDY GIRL™
PART NUMBER	25224	25153
UL & ULC RATING	1A:10B:C	1A:10B:C
CAPACITY (LBS.)	2.5	2.5
SHIPPING WT. (LBS.)	5.25/5.5	5.25/5.5
HEIGHT (IN.)	15.5	15.5
WIDTH (IN.)	5.75	5.75
DEPTH (IN.)	3	3
RANGE (INITIAL - FT)	9-15	9-15
DISCHARGE TIME (SEC.)	10	10
INCLUDED BRACKET	WALL/VEHICLE	WALL/VEHICLE