

## GPCZ.EX2764 Dry-chemical Extinguishers, Portable, Marine

Page Bottom

### Dry-chemical Extinguishers, Portable, Marine

See General Information for Dry-chemical Extinguishers, Portable, Marine

**AMEREX CORP**

7595 GADSDEN HWY E  
PO BOX 81  
TRUSSVILLE, AL 35173 USA

EX2764

#### Stored-pressure-type Extinguishers

Model	Nominal Agent Capacity lb	Min Use Temp, °F	Rating	Marine Classification	
				Type A Size	Type B:C Size
<b>Ammonium phosphate</b>					
B417	2.5	-65	1-A:10-B:C	—	I
B424, B500	5	-65	2-A:10-B:C	II	I
B402	5	-65	3-A:40-B:C	II	I
B461, B443	6	-65	3-A:40-B:C	II	I
B456, B441	10	-65	4-A:80-B:C	II	II
592	13.2	-65	4-A:80-B:C	II	II
594	13.2	-65	2-A:40-B:C	II	II
581	20	-65	4-A:40-B:C	II	III
423, 564, A411	20	-65	10-A:120-B:C	II	III
589	30	-65	10-A:160-B:C	II	IV
567	30	-65	4-A:40-B:C	II	IV
763	30	-65	4-A:80-B:C	II	IV
<b>Potassium Bicarbonate</b>					
B410	2.5	-65	10-B:C	—	I
B416	5	-65	10-B:C	—	I
B479	5	-65	30-B:C	—	I
B460	10	-65	80-B:C	—	II
595	13.2	-65	40-B:C	—	II
599	13.2	-65	80-B:C	—	II
584	20	-65	20-B:C	—	III
580	20	-65	40-B:C	—	III
566, A413, 415	20	-65	120-B:C	—	III
569	30	-65	40-B:C	—	IV
764	30	-65	80-B:C	—	IV
693	30	-65	120-B:C	—	IV
591	30	-65	160-B:C	—	IV
<b>Sodium bicarbonate</b>					
B403, C403	2.5	-65	10-B:C	—	I

B409	5	-65	10-B:C	—	I
B453	5.5	-65	40-B:C	—	I
B459, B462	6	-65	40-B:C	—	I
B457, B447	10	-65	60-B:C	—	II
593	13.2	-65	40-B:C	—	II
A412, 408	20	-65	120-B:C	—	III
582	20	-65	40-B:C	—	III
568	30	-65	40-B:C	—	IV

Last Updated on 2011-06-16

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

© 2012 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".